

**PRIOR TO USE, PLEASE REGISTER YOUR CK-MINI MACHINE
AT WWW.VSEGLOBAL.COM/WARRANTY**

READ USER MANUAL PRIOR TO USE

1. Remove ALL packing Materials from the CK-Mini Machine.

Do NOT attempt to run the machine with plastic shipping bag or any other materials blocking the blower intake (located on bottom of machine.) Blocking air flow to the machine could cause irreversible damage to the machine and create a fire hazard.

2. Attach the blower hose by lining up the hose collar with the fitting on the machine and gently the collar clockwise. Hand tighten until snug; do not torque or use tools to secure.
3. Attach the fluid delivery line by removing blue retainer clip and then inserting the clear line into the white quick connect fitting located on top of the CK-Mini Machine.
4. Replace the blue retainer clip and gently pull back on the fluid line to ensure the fitting is secure.
5. Remove the cap from the fluid reservoir by turning counterclockwise. Then, fill tank with approximately 1 / 2 gallon of approved disinfectant fluid.
6. Replace reservoir cap and hand tighten to a snug fit.
7. Plug in the CK-Mini Machine power cord into a 120V 60Hz outlet.
8. Grasp the nozzle from the end of the blower hose and point in desired direction.
9. Apply power to the CK-Mini Machine by pressing the power toggle switch and flipping to the "I" or ON position.

Do NOT attempt to run the machine without fluid in the reservoir. This may cause irreversible damage to the machine and void the warranty.

10. Use the flow control valve above the power switch to adjust the fluid delivery amount
 - The aerosol mist should leave the application nozzle as a fine spray in order to coat surfaces properly.
 - A heavier spray can drip and accumulate on the ground causing slippery conditions and should NOT be necessary to adequately treat surfaces.

Personal protective equipment should **ALWAYS** be utilized when using this machine to disperse chemicals. Refer to your chemical product label for additional safety information.